# Mira Element EV

Mixer Shower

Its simple, uncluttered look is ideal for a contemporary or family bathroom, plus its single control makes it easy to use.

#### **Product Information**

Description	Colour	Product No.
Mira Element EV	Chrome	1.1910.001
Mira Element Exposed Valve only	Chrome	1.1910.002

### Features & Benefits

Temperature control
Thermostatic temperature stability certified to TMV2
Easy to fit
Quickly and easily fits onto reversed inlet supplies
Adjustable slide bar fits over holes left by previous shower kit (400mm-600mm)
Easy to service
Easily replaceable pull out large, long-life filters
Patented 'easy clip' system makes the cartridge easy to replace
For your customer
Single control for flow and temperature
Space saving refined slim valve maximises showering space
Mira Magni-flo™ technology delivers up to 3x more flow, even at low pressure
Large 4 spray 11m showerhead with rub-clean nozzles



SUITABLE FOR ALL SYSTEMS



YEAR GUARANTEE

#### Tech Details

Temperature control Control type: Thermostatic Installation

Water entry points: Rising, falling or rear

Inlet connections: 15 mm compression (EV, BIV & BIR)

Outlet connections:  $\ensuremath{\mathscr{V}}^{\prime\prime}$  BSP Male Flat Face (EV) or 15mm compression (BIV & BIR)

Reversed inlets supported: Yes

Supply Conditions (hot and cold)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating)

55°C-65°C (recommended)

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

## Performance

Flow rate (Rain+ spray at handset): 11.1 l/min at 0.5 bar, Valve only: 17.3 l/min at 0.5 bar

Temperature stability: ± 2°C

#### Safety Feature

Automatic shutdown: Shutdown within 2 secs

Factory set to safe max temp: Factory set to 41°C

Adjustable maximum temperature for on-site conditions

Approvals

WRAS approved (Water Regulations Advisory Scheme)

TMV2 certified



#### Dimensions



